

Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 952 394 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
27.10.1999 Bulletin 1999/43

(51) Int. Cl.⁶: F23G 5/08, F23J 15/02

(21) Application number: 99107186.1

(22) Date of filing: 13.04.1999

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• Yamada, Yasuhiro
Osaka (JP)
• Takeda, Masuo
Fukuoka-shi, Fukuoka (JP)

(30) Priority: 16.04.1998 JP 10645098
11.06.1998 JP 16359298

(74) Representative:
Eder, Eugen, Dipl.-Ing.
Patentanwälte
Eder & Schieschke
Elisabethstrasse 34
80796 München (DE)


(71) Applicant:
Innovative Environmental Technology Co., Ltd.
Fukuoka-shi, Fukuoka (JP)

(54) Waste incinerator

(57) A waste incinerator which can completely prevent environmental pollution by dioxins. Exhaust gas from an incinerator (1) is guided into a glass melting furnace (2) by a duct (3), and blown into molten glass (8) through a bubbling pipe (7) to decompose dioxins in the exhaust gas. High-temperature gas produced in the glass melting furnace is supplied into the incinerator by a pipe to burn wastes without using auxiliary fuel. Fur-

ther, exhaust gas is pressurized by pressure pumps (10,11) in a pipe (9) branching from the duct, while fuel tablets (40) to which are added ashes are introduced through a fuel inlet (12) and fed into the molten glass under the pressure of exhaust gas to decompose dioxins in the ashes.

FIG. 1



EP 0 952 394 A2

Description

BACKGROUND OF THE INVENTION

[0001] This invention relates to a waste incinerator especially suitable for preventing environmental pollution by dioxin.

[0002] Environmental pollution by dioxin produced when industrial and other wastes burn is becoming one of the biggest social problems in recent years. Dioxine is a general term for virulently poisonous isomers having a molecular structure consisting of two benzene rings bonded together by two oxygen atoms, and chlorine atoms bonded to the benzene rings. Dioxins are produced in large amounts especially when plastics containing chlorine are burned. Dioxins not only pollute the atmosphere but soil and water by falling onto the ground. Waste ashes are also a leading cause of soil pollution because they also contain a large amount of dioxin.

[0003] Just recently, it was found out that the higher the burning temperature of wastes, the less they produce dioxins. Thus, the best way to reduce the dioxin content is to burn wastes at as high a temperature as possible. But a high-temperature incinerator tends to be large in scale, and needs a complicated heat-shield structure. Its running cost is high too because heavy oil is used. Further, although such a high-temperature incinerator can reduce the production of dioxins, exhaust gases and ashes produced from such an incinerator still contain a certain amount of dioxins, so that it is impossible to totally prevent environmental pollution by dioxins.

[0004] An object of this invention is to provide a waste incinerator which can completely prevent environmental pollution by dioxins.

SUMMARY OF THE INVENTION

[0005] According to this invention, there is provided a waste incinerating apparatus comprising an incinerator and a glass or metal melting furnace arranged such that exhaust gas discharged from the incinerator is blown into molten glass or metal in the melting furnace.

[0006] The exhaust gas discharged from the incinerator is blown into high-temperature molten glass or metal to decompose poisonous dioxins in the exhaust gas. The high-temperature molten material also decomposes polychlorinated biphenyl contained in the exhaust gas. If the material is molten glass, it is possible to remove carbon dioxide, nitrogen oxides, sulfur oxides, lead, arsenic and other heavy metal oxides, halogens, etc. by melting them into the molten glass.

[0007] By bubbling the exhaust gas blown into the molten material from a lower portion of the melting furnace while maintaining the molten material at 850 °C or over, dioxins can be decomposed more completely because dioxins is kept in contact with the high-temper-

ature material efficiently for a long time. The molten material is maintained at a temperature not less than 850°C because it is known that dioxins can be completely decomposed by maintaining them at a temperature of 850°C or over for 2 seconds. Glass and most metals have a melting point of 850°C and over. But if a metal having a melting point lower than 850°C is used as the molten material, it has to be heated to 850 °C or over.

[0008] By providing at least one porous or mesh plate in the molten material, it is possible to cut bubbles of exhaust gas blown into the molten material into small pieces, so that dioxins can be brought into contact with the high-temperature material with higher efficiency.

[0009] By supplying the high-temperature gas produced in the melting furnace into the incinerator, the combustion efficiency in the incinerator improves. This eliminates the need for auxiliary fuel, and makes it possible to use thermal energy efficiently.

[0010] By pressurizing the exhaust gas discharged from the incinerator, and providing a fuel inlet at an intermediate portion of a pipe through which the pressurized exhaust is guided into the molten material in the melting furnace, it is possible to supply fuel through the fuel inlet into the molten material using the pressure of the pressurized exhaust gas to use the fuel as a heat source for the melting furnace.

[0011] Fuel supplied through the fuel inlet may be formed by solidifying waste plastic or a mix of waste plastic and pulverized glass, waste ashes or polluted soil to use the waste plastic as a heat source for the melting furnace and to decompose dioxins produced from the waste plastic.

[0012] By adding waste ashes and polluted soil to the waste plastic, it is possible to treat these flame-retardant wastes in the high-temperature molten material. By adding waste ashes discharged from the incinerator, it is possible to decompose dioxins contained in the ashes. By adding glass powder to the waste plastic, it is possible to eliminate the need to replenish glass material into the glass melting furnace.

[0013] Other features and objects of the present invention will become apparent from the following description made with reference to the accompanying drawings, in which:

BRIEF DESCRIPTION OF THE DRAWINGS

[0014]

Fig. 1 is a schematic view showing a waste incinerating apparatus embodying the invention;

Fig. 2 is a sectional view along line II-II of Fig. 1; and

Fig. 3 is a schematic view showing how fuel tablets are formed.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0015] Now referring to Figs. 1 through 3, an embodiment of this invention is described. The waste incinerating apparatus of the embodiment comprises an incinerator 1 and a glass melting furnace 2. Exhaust gas of the incinerator 1 is guided by a duct 3 through a pressure pump 4 into an exhaust gas adjusting tank 5. It is then further pressurized by a pressure pump 6 and blown to the bottom of molten glass 8 in the glass melting furnace 2 through a bubbling pipe 7. Another pipe 9 is connected to the exhaust gas adjusting tank 5. Exhaust gas is also pressurized by pressure pumps 10, 11 and introduced into the molten glass 8 through this pipe 9. A pipe 13 extends from an intermediate portion of the pipe 9 to a fuel inlet 12 which is described later.

[0016] To the top of the glass melting furnace 2, three pipes 14, 15, 16 are connected. In order to improve heat insulating properties, the pipes 14 and 15 comprise an inner pipe 17 made of molybdenum and an outer pipe 18 with the space 19 between the inner and outer pipes depressurized. The pipe 14 is connected through a pressurizing tank 20 to the lower part of the incinerator 1 to supply hot air into the incinerator. Hot air from the pipe 15 is also supplied to a private power generator 21 and used as a heat source for its steam turbine. The pipe 16 extends to a scrubber 22, where the chlorine gas produced by decomposing dioxins is neutralized. A vacuum pump 23 is provided in the pipe 16 to depressurize the interior of the glass melting furnace 2 so that exhaust gas from the bubbling pipe 7 can be easily introduced into the molten glass 8.

[0017] The incinerator 1 has furnace beds 24 in three tiers. Wastes 25 to be burned are fed onto the beds 24 through respective chutes 26. Each chute 26 has at its inlet a check valve 27 made of heat-resistant rubber. The incinerator 1 and the duct 3 have their inner walls lined with heat-resistant bricks 28. A filter 29 is provided at the inlet of the duct 3 to remove dust.

[0018] The bubbling pipe 7 connected to the bottom of the glass melting furnace 2 comprises, see Fig. 2, an annular pipe 30 and a plurality of radial pipes 31 of different lengths connected to the pipe 30 so that exhaust gas outlets 32 are distributed uniformly in a horizontal section of the glass melting furnace 2.

[0019] Three mesh plates 33, 34, 35 are provided one over another in the molten glass 8. These mesh plates serve to cut bubbles of exhaust gas blown in from the bubbling pipe 7 into small pieces. Since bubbles grow as they rise by merging and depressurization, the upper mesh plate is finer in mesh than the one immediately thereunder. The uppermost mesh plate 33 has a V section so that molten dregs will collect at the ends of the surface of the molten glass 8.

[0020] In the hot molten glass 8, polychlorinated biphenyl is decomposed together with dioxins. Also, carbon dioxide, nitrogen oxides, sulfur oxides, lead,

arsenic and other heavy metal oxides, halogens, etc. contained in the exhaust gas melt into the molten glass 8 and are removed.

[0021] An overflow port 36 is provided at top of the glass melting furnace 2. A pipe 37 connects the port 36 to a glass sorting device 38. Molten glass 8 flowing out through the overflow port 36 is cooled and sorted in the sorting device 38 and used for e.g. craftwork.

[0022] In the pipe 13 leading to the fuel inlet 12, check valves 39 made of heat-resistant rubber are provided in three stages. Fuel tablets 40 introduced through the fuel inlet 12 drop through the pipe 13 and fed into the molten glass 8 by the pressurized exhaust gas.

[0023] As shown in Fig. 3, fuel tablets 40 are formed by crushing waste plastic in a crusher 42, adding pulverized glass 43 and ashes 44 to the crushed waste plastic 41, and compressing the mix in a press 45. Pulverized glass 43 is added to supply glass material into the furnace 2, increase the melting point of the tablets 40, prevent the tablets from melting in the pipe 13 and thus to smoothly feed the tablets 40 into the glass melting furnace. Also, pulverized glass 43 serves to neutralize acidic ashes 44 by melting in the glass melting furnace 2.

[0024] The ashes 44 may be ashes discharged from the incinerator 1 or existing unprocessed ashes. Fuel tablets 40 are formed by solidifying a mix of different kinds of powders in this embodiment, but may be formed by solidifying different kinds of powders in layers. For example, each tablet may comprise an inner layer of waste plastic 41 and ashes 44, and an outer layer of pulverized glass 43.

[0025] The incinerator of the embodiment is a glass melting furnace. But a metal melting furnace may be used instead. As a metal melting furnace, a melting furnace for melting scraps or a furnace for treating molten metals such as a converter for steel may be used.

[0026] The incinerator is not limited to the type having multiple tiers of beds as in the embodiment, but may be of any other type. Of course, an incinerator that needs auxiliary fuel may be used. A chimney of an existing incinerator may be modified into a duct to guide exhaust gas into the melting furnace.

[0027] As described above, according to this invention, exhaust gas from the incinerator is guided into a glass or metal melting furnace so as to be blown into the hot molten body to decompose virulently poisonous dioxins. It is thus possible to completely prevent environmental pollution by dioxins contained in exhaust gas.

This incinerator can also decompose poisonous polychlorinated biphenyl. If a glass melting furnace is used, it is possible to remove carbon dioxide, nitrogen oxides, sulfur oxides, lead, arsenic and other heavy metal oxides, halogens, etc. by melting them into the molten glass.

[0028] Since hot gas produced in the melting furnace is supplied into the incinerator, the burning efficiency in the incinerator improves, so that no auxiliary fuel is

needed. Thermal energy can thus be efficiently used. Since exhaust gas from the incinerator is pressurized and a fuel inlet is provided in an intermediate portion of the pipe through which the pressurized exhaust gas is guided into the melting furnace, it is possible to supply waste plastic through this inlet to use it as a heat source for the melting furnace. By adding ashes to the waste plastic, it is possible to decompose dioxins in the ashes.

Claims

10

1. A waste incinerating apparatus comprising an incinerator and a glass or metal melting furnace arranged such that exhaust gas discharged from said incinerator is blown into molten glass or metal in said melting furnace. 15
2. The apparatus as claimed in claim 1 wherein said molten glass or metal is maintained at 850 °C or higher, and wherein said exhaust gas is blown into the molten glass or metal from a lower portion of said melting furnace while bubbling. 20
3. The apparatus as claimed in claim 1 or 2 wherein at least one porous or mesh plate is provided in said melting furnace. 25
4. The apparatus as claimed in any of claims 1 through 3 wherein high-temperature gas produced in said melting furnace is supplied into said incinerator. 30
5. The apparatus as claimed in any of claims 1 through 4 wherein exhaust gas discharged from said incinerator is pressurized, and wherein a fuel inlet is provided in an intermediate portion of a pipe through which the pressurized exhaust gas is introduced into said melting furnace. 35
6. The apparatus as claimed in claim 5 wherein fuel supplied through said fuel inlet is formed by solidifying waste plastic or a mix of waste plastic and pulverized glass, ashes or polluted soil. 40

45

50

55

FIG. 1




FIG. 2




FIG. 3

